



POLY BAG SEALER GUIDE

TABLETOP

						
LOW TO MEDIUM VOLUME	Tabletop	Tabletop with Cutter	Deluxe Tabletop with Cutter	Beep Impulse	Extra Long Tabletop	Extra Long Tabletop with Cutter
Sealer Type	Impulse	Impulse	Impulse	Impulse	Impulse	Impulse
Max. Seal Thickness	8 mil					
Seal Size (L x W)	4 x 1/16" 8 x 1/16" 12 x 1/16" 16 x 1/16" 20 x 1/16"	8 x 1/16" 12 x 1/16" 16 x 1/16" 20 x 1/16"	12 x 1/16" 16 x 1/16" 24 x 1/16"	8 x 1/16" 12 x 1/16"	24 x 1/16" 32 x 1/16"	24 x 1/16"
Usage	Up to 10 seals per minute	Up to 10 seals per minute	Up to 10 seals per minute	Up to 5 seals per minute	Up to 5 seals per minute	Up to 5 seals per minute
Operation	Spring Activation	Spring Activation	Magnetic Activation	Spring Activation	Spring Activation	Spring Activation
Compatible Materials	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)
Incompatible Materials	Vinyl Bags, Wax Bags					
Temperature Range	446-464° F	446-464° F	212-320° F	464-480° F	176-428° F	464-480° F
Price	\$	\$\$	\$\$\$	\$	\$\$\$	\$\$\$
Built-In Cutter		✓	✓			✓
Adjustable Timer	✓	✓	✓	✓	✓	✓
Additional Features			<ul style="list-style-type: none"> Fewer moving parts and less wiring for reduced maintenance Optional working table 	<ul style="list-style-type: none"> Beep sound 	<ul style="list-style-type: none"> Carry handle for portability 	

1-800-295-5510 uline.com

FOOT-OPERATED

	 Foot-Operated	 Foot-Operated with Cutter	 Deluxe Foot-Operated	 Extra Long Foot-Operated
HIGH VOLUME				
Sealer Type	Impulse	Impulse	Impulse	Impulse
Max. Seal Thickness	8 mil	8 mil	8 mil	8 mil
Seal Size (L x W)	12 x 1/16" 18 x 1/16" 24 x 1/16"	18 x 1/16" 24 x 1/16"	16 x 3/16" 24 x 3/16"	30 x 1/16"
Usage	Up to 10 seals per minute	Up to 5 seals per minute	Up to 10 seals per minute	Up to 5 seals per minute
Operation	Pedal Activation	Pedal Activation	Pedal Activation	Pedal Activation
Compatible Materials	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)	Mylar, Nylon, PVC, Static Shielding, Foam (up to 1/8" thick), Polypropylene, Polyurethane, Polyethylene, Metalized Food Bags (up to 2.5 mil)
Incompatible Materials	Vinyl Bags, Wax Bags			
Temperature Range	446-464° F	176-428° F	212-320° F	446-464° F
Price	\$	\$\$	\$\$\$	\$\$
Built-In Cutter		✓	✓	
Adjustable Timer	✓	✓	✓	✓
Overall Height Options	35"	36", 37½"	43½"	34½"
Additional Features	<ul style="list-style-type: none"> Adjustable height working tray 	<ul style="list-style-type: none"> Roll dispenser Stationary working tray 	<ul style="list-style-type: none"> Fewer moving parts and less wiring for reduced maintenance Poly tubing holder 	<ul style="list-style-type: none"> Adjustable height working tray

HANDHELD



Crimper Hand

Sealer Type	Constant
Max. Seal Thickness	10 mil
Seal Size (L x W)	6 x 1/2"
Operation	Manually Controlled
Compatible Materials	High Clarity Polypropylene, Cellophane, Metalized Food Bags, Barrier Pouches
Incompatible Materials	Polyethylene, Fabric, Tyvek Bags, Wax Bags
Temperature Range	284-392° F
Price	\$
Adjustable Timer	N/A
Additional Features	<ul style="list-style-type: none"> • On/off safety switch • Foot pedal