

.....I @B9 PAINT MARKER! Yellow

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 07/27/2015
Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Paint.

1.3. Supplier information

Wä ^Á Canada Corp
3333 James Snow Parkway NorthÁ
Milton, ON L9T 8L1
Canada
Phone: 1-800-661-6611

1.4. Emergency telephone number

24-hour emergency: CHEMTREC- US/Canada: 1-800-424-9300
International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % (w/w) | GHS-US classification |
|---|---------------------|--|--|
| tert-butyl acetate | (CAS No) 540-88-5 | 41.14 – 41.35 Yellow 36.47 – 36.65 Light Blue | Flam. Liq. 2, H225 |
| Cyclohexanone | (CAS No) 108-94-1 | 9.82 Yellow 3.08 Light Blue | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 |
| Butyl acetate | (CAS No) 123-86-4 | 3.81 – 4.64 Yellow 3.12 – 3.9 Light Blue | Flam. Liq. 3, H226 STOT SE 3, H336 |
| 2-methoxy-1-methylethyl acetate | (CAS No) 108-65-6 | 0.52 – 1.03 Yellow 1.14 – 2.28 Light Blue | Flam. Liq. 3, H226 |
| Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) | (CAS No) 64742-48-9 | 1.32 Yellow 1.23 Light Blue | Flam. Liq. 4, H227 Asp. Tox. 1, H304 |
| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) | (CAS No) 64742-95-6 | 0.15 – 0.74 Yellow 0.12 – 0.59 Light Blue | Asp. Tox. 1, H304 |
| 1,2,4-trimethylbenzene | (CAS No) 95-63-6 | 0.15 – 0.74 Yellow 0.12 – 0.59 Light Blue | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Chronic 2, H411 |

Full text of H-statements: see section 16

I LINE PAINT MARKER! Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Get medical advice/attention if you feel unwell |
| First-aid measures after inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| First-aid measures after skin contact | : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. |
| First-aid measures after eye contact | : In case of contact, immediately flush eyes with plenty of water. |
| First-aid measures after ingestion | : Rinse mouth. Do NOT induce vomiting. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------|---------------|
| Symptoms/injuries | : None known. |
|-------------------|---------------|

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing media appropriate for surrounding fire. |
| Unsuitable extinguishing media | : None known. |

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|--|
| Fire hazard | : Flammable liquid and vapour. |
| Explosion hazard | : May form flammable/explosive vapour-air mixture. |
| Reactivity | : No dangerous reactions known. |

5.3. Advice for firefighters

| | |
|--------------------------------|---|
| Firefighting instructions | : Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--|
| General measures | : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist. |
|------------------|--|

6.1.1. For non-emergency personnel

| | |
|----------------------|-----------------------------------|
| Emergency procedures | : Evacuate unnecessary personnel. |
|----------------------|-----------------------------------|

6.1.2. For emergency responders

| | |
|----------------------|---|
| Emergency procedures | : Stop leak if safe to do so. Ventilate area. |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| Methods for cleaning up | : Wipe up with absorbent material (for example cloth). |
|-------------------------|--|

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|---|
| Additional hazards when processed | : Handle empty containers with care because residual vapours are flammable. |
| Precautions for safe handling | : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. |
| Hygiene measures | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. |

I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

7.2. Conditions for safe storage, including any incompatibilities

| | |
|-------------------------------|---|
| Technical measures | : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. |
| Storage conditions | : Keep container closed when not in use. |
| Incompatible products | : Oxidizing agent. Acids. Alkali. Moisture. |
| Incompatible materials | : Heat sources. |
| Heat and ignition sources | : Keep away from heat, sparks and flame. |
| Prohibitions on mixed storage | : Incompatible materials. |
| Storage area | : Store in dry, cool, well-ventilated area. |

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Uline Paint Marker | | |
|--|------------------------|---------------|
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| Butyl acetate (123-86-4) | | |
| ACGIH | ACGIH TWA (mg/m³) | 713 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 150 ppm |
| ACGIH | ACGIH STEL (mg/m³) | 950 mg/m³ |
| ACGIH | ACGIH STEL (ppm) | 200 ppm |
| ACGIH | Remark (ACGIH) | Eye & URT irr |
| OSHA | OSHA PEL (TWA) (mg/m³) | 710 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 150 ppm |
| Canada (Quebec) | VECD (mg/m³) | 950 mg/m³ |
| Canada (Quebec) | VECD (ppm) | 200 ppm |
| Canada (Quebec) | VEMP (mg/m³) | 713 mg/m³ |
| Canada (Quebec) | VEMP (ppm) | 150 ppm |
| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| 1,2,4-trimethylbenzene (95-63-6) | | |
| ACGIH | ACGIH TWA (mg/m³) | 123 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 25 ppm |
| OSHA | Not applicable | |
| Canada (Quebec) | VECD (mg/m³) | 172 mg/m³ |
| Canada (Quebec) | VECD (ppm) | 35 ppm |
| Canada (Quebec) | VEMP (mg/m³) | 123 mg/m³ |
| Canada (Quebec) | VEMP (ppm) | 25 ppm |
| tert-butyl acetate (540-88-5) | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| Cyclohexanone (108-94-1) | | |
| ACGIH | ACGIH TWA (mg/m³) | 50 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | ACGIH STEL (ppm) | 50 ppm |
| ACGIH | Remark (ACGIH) | Eye & URT irr |
| OSHA | OSHA PEL (TWA) (mg/m³) | 200 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 50 ppm |

I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

| Cyclohexanone (108-94-1) | | |
|---|-----------------------|-----------|
| Canada (Quebec) | VEMP (mg/m³) | 100 mg/m³ |
| Canada (Quebec) | VEMP (ppm) | 25 ppm |
| Canada (Quebec) | Notations and remarks | (Peau) |
| 2-methoxy-1-methylethyl acetate (108-65-6) | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9) | | |
| ACGIH | ACGIH TWA (mg/m³) | 5 mg/m³ |
| ACGIH | ACGIH STEL (mg/m³) | 10 mg/m³ |
| OSHA | Not applicable | |

8.2. Exposure controls

| | |
|----------------------------------|---|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Hand protection | : None under normal use. |
| Eye protection | : None under normal use. |
| Respiratory protection | : None under normal use. |
| Other information | : Do not eat, drink or smoke when using this product. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Appearance | : Solid marker containing liquid colored paint. |
| Colour | : Variable. |
| Odour | : Solvent. |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : 23 - 37.8 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

| | |
|-------------|--------|
| VOC content | : 67 % |
|-------------|--------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

Oxidizer. Acids. Alkali. Moisture.

10.6. Hazardous decomposition products

May release flammable gases. Thermal decomposition generates : metallic oxides. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Butyl acetate (123-86-4) | |
|--|----------------------------|
| LD50 oral rat | 10760 mg/kg |
| LD50 dermal rabbit | > 14112 mg/kg |
| LC50 inhalation rat (mg/l) | > 21 mg/l/4h |
| ATE CLP (oral) | 10760.000 mg/kg bodyweight |
| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | |
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | > 5610 mg/l/4h |
| 1,2,4-trimethylbenzene (95-63-6) | |
| LD50 oral rat | 3415 mg/kg |
| LD50 dermal rat | 3440 mg/kg |
| LC50 inhalation rat (ppm) | 954 ppm |
| ATE CLP (oral) | 3415.000 mg/kg bodyweight |
| ATE CLP (dermal) | 3440.000 mg/kg bodyweight |
| ATE CLP (dust,mist) | 1.500 mg/l/4h |
| tert-butyl acetate (540-88-5) | |
| LD50 oral rat | 4100 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (ppm) | 4211 ppm 6 h |
| ATE CLP (oral) | 4100.000 mg/kg bodyweight |
| Cyclohexanone (108-94-1) | |
| ATE CLP (dust,mist) | 1.500 mg/l/4h |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| LD50 oral rat | 8532 mg/kg |
| LD50 dermal rat | > 2000 mg/kg |
| LC50 inhalation rat (ppm) | 4345 ppm 6 h |
| ATE CLP (oral) | 8532.000 mg/kg bodyweight |
| Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9) | |
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | > 5610 mg/m ³ |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

| Cyclohexanone (108-94-1) | |
|--------------------------|----------------------|
| IARC group | 3 - Not classifiable |

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Aspiration hazard : Not classified
Potential adverse human health effects and symptoms
Likely routes of exposure : Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | |
|--|-----------------|
| LC50 fish 1 | 8.2 mg/l |
| EC50 Daphnia 1 | 4.5 mg/l |
| EC50 other aquatic organisms 1 | 3.7 mg/l |
| NOEC (acute) | 0.5 mg/l |
| 1,2,4-trimethylbenzene (95-63-6) | |
| LC50 fish 1 | 7.72 mg/l |
| LC50 other aquatic organisms 1 | 3.6 mg/l |
| EC50 other aquatic organisms 1 | 2.356 mg/l |
| tert-butyl acetate (540-88-5) | |
| LC50 fish 1 | 240 mg/l 96 h |
| EC50 Daphnia 1 | 410 mg/l 24 h |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| LC50 fish 1 | 100 - 180 mg/l |
| EC50 Daphnia 1 | > 500 mg/l 48 h |
| ErC50 (algae) | > 1000 mg/l |
| Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9) | |
| LC50 fish 1 | 8.2 mg/l |

12.2. Persistence and degradability

| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | |
|--|------------------------|
| Persistence and degradability | Not established. |
| tert-butyl acetate (540-88-5) | |
| Persistence and degradability | Readily biodegradable. |
| Biodegradation | 50 % 28 d |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| Persistence and degradability | Readily biodegradable. |
| Biodegradation | 89 % 10 d |

12.3. Bioaccumulative potential

| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | |
|--|------------------|
| Bioaccumulative potential | Not established. |
| tert-butyl acetate (540-88-5) | |
| BCF fish 1 | 5.61 |
| Log Pow | 1.64 |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| Log Pow | 0.43 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable.

I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 14: Transport information

In accordance with DOT and TDG

| | |
|----------------------------------|--|
| Transport document description | : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III |
| UN-No.(DOT) | : UN1263 |
| Proper Shipping Name (DOT) | : Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base |
| Transport hazard class(es) (DOT) | : 3 - Flammable liquid |
| Packing group (DOT) | : III - Minor Danger |

ADR

| | |
|--------------------------------|--------------------------------|
| Transport document description | : UN 1263 PAINT, 3, III, (D/E) |
| Proper Shipping Name (ADR) | : PAINT |
| Packing group (ADR) | : III |
| Class (ADR) | : 3 - Flammable liquid |

Transport by sea

| | |
|-----------------------------|-------------------------|
| UN-No. (IMDG) | : UN 1263 |
| Proper Shipping Name (IMDG) | : PAINT |
| Class (IMDG) | : 3 - Flammable liquids |
| Packing group (IMDG) | : III |

Air transport

| | |
|-----------------------------|-------------------------|
| UN-No. (IATA) | : UN 1263 |
| Proper Shipping Name (IATA) | : Paint |
| Class (IATA) | : 3 - Flammable Liquids |
| Packing group (IATA) | : III |

SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|--|---------|
| Butyl acetate (123-86-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 5000 lb |
| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| 1,2,4-trimethylbenzene (95-63-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| tert-butyl acetate (540-88-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Cyclohexanone (108-94-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

15.2. International regulations

CANADA

| | |
|--|--|
| Butyl acetate (123-86-4) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| 1,2,4-trimethylbenzene (95-63-6) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |
| tert-butyl acetate (540-88-5) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |

I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Cyclohexanone (108-94-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-methoxy-1-methylethyl acetate (108-65-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Butyl acetate (123-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene < 0.1%) (64742-95-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1,2,4-trimethylbenzene (95-63-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

tert-butyl acetate (540-88-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Cyclohexanone (108-94-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

2-methoxy-1-methylethyl acetate (108-65-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Uline Paint Marker

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

Butyl acetate (123-86-4)

U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - List of Hazardous Substances

tert-butyl acetate (540-88-5)

U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Right to Know List of Hazardous Chemicals
U.S. - Pennsylvania - List of Hazardous Substances

Cyclohexanone (108-94-1)

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New York - Right to Know List of Hazardous Chemicals
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Minnesota - Hazardous Substance List

SECTION 16: Other information

Indication of changes

: Original document.

Data sources

: ACGIH (American Conference of Government Industrial Hygienists).

European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.

National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.

OSHA 29CFR 1910.1200 Hazard Communication Standard.

TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.


I @B9'D5-BH'A5F?9F!MY`ck

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

| | |
|----------------------------|--|
| Abbreviations and acronyms | : ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. TWA: Time Weight Average. TSCA: Toxic Substances Control Act. |
| Other information | : None. |

| | |
|--------------------|---|
| NFPA health hazard | : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given. |
| NFPA fire hazard | : 1 - Must be preheated before ignition can occur. |
| NFPA reactivity | : 0 - Normally stable, even under fire exposure conditions, and not reactive with water. |



Full text of H-statements:

| | |
|---------------------------|--|
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment — Chronic Hazard, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Flam. Liq. 4 | Flammable liquids, Category 4 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H227 | Combustible liquid |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H411 | Toxic to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product