

### **Safety Data Sheet**

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 05-6638-0
 Version Number:
 13.00

 Issue Date:
 06/26/18
 Supercedes Date:
 06/21/17

**Product identifier** 

3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP100 Plus Clear

 ID Number
 UPC
 ID Number
 UPC

 62-3272-1430-0
 62-3272-1431-8

 62-3272-1435-9
 62-3272-1436-7

 62-3272-3530-5
 62-3272-3830-9

### Recommended use

Structural adhesive

### Supplier's details

MANUFACTURER: 3M

**DIVISION:** Industrial Adhesives and Tapes Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

### **Emergency telephone number**

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

05-6631-5, 05-6630-7

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com



## **Safety Data Sheet**

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 05-6630-7
 Version Number:
 18.00

 Issue Date:
 06/26/18
 Supercedes Date:
 06/08/18

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive DP100 Plus Clear, Part A

### 1.2. Recommended use and restrictions on use

### Recommended use

Structural adhesive

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Industrial Adhesives and Tapes Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

#### 2.1. Hazard classification

Skin Sensitizer: Category 1A.

#### 2.2. Label elements

Signal word

Warning

### **Symbols**

Exclamation mark |

### **Pictograms**



n.... 1 .e.

### **Hazard Statements**

May cause an allergic skin reaction.

### **Precautionary Statements**

### **Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

### **Response:**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

## **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Mercaptan Polymer	72244-98-5	90 - 99 Trade Secret *
Propyleneoxide modified polyamine	Trade Secret*	1 - 10 Trade Secret *
bis(Dimethylaminoethyl) ether	3033-62-3	< 1.5 Trade Secret *
Triethylenetetramine	112-24-3	< 1 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **Inhalation:**

No need for first aid is anticipated.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

No need for first aid is anticipated.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Sulfide	During Combustion
Oxides of Sulfur	During Combustion

### **5.3.** Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Triethylenetetramine	112-24-3	AIHA	TWA:6 mg/m3(1 ppm)	SKIN
bis(Dimethylaminoethyl) ether	3033-62-3	ACGIH	TWA:0.05 ppm;STEL:0.15	SKIN
			ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Neoprene

#### Respiratory protection

None required.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**General Physical Form:** Liquid **Specific Physical Form:** Viscous

Odor, Color, Grade: Clear; mercaptan odor **Odor threshold** No Data Available pН Not Applicable Melting point Not Applicable **Boiling Point** Not Applicable

**Flash Point** >=115 °C [Test Method: Estimated]

**Evaporation rate** Not Applicable Not Applicable Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable

Vapor Pressure <=0.01 mmHg [@ 20 °C]

Vapor Density Not Applicable 1.15 g/ml **Density** 

06/26/18

Specific Gravity 1.15 [Ref Std:WATER=1]

Solubility in Water Negligible

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data Available

**Viscosity** 19,400 centipoise [@ 20 °C ]

Hazardous Air Pollutants 0 % weight [Test Method: Calculated]

Molecular weight No Data Available

VOC Less H2O & Exempt Solvents 7.8 g/l [Test Method:calculated SCAQMD rule 443.1]

[Details: when used as intended with Part B]

**VOC Less H2O & Exempt Solvents** 0.7 % [Test Method: calculated per CARB title 2] [Details: when

used as intended with Part B]

VOC Less H2O & Exempt Solvents 15.6 g/l [Test Method:calculated SCAQMD rule 443.1]

[Details: as supplied]

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

#### 10.5. Incompatible materials

None known.

#### 10.6. Hazardous decomposition products

**Substance** Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

No known health effects.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

May be harmful if swallowed.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value		
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg		
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l		
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg		
Mercaptan Polymer	Dermal	Rabbit	LD50 > 10,200 mg/kg		
Mercaptan Polymer	Ingestion	Rat	LD50 2,600 mg/kg		
bis(Dimethylaminoethyl) ether	Dermal	Rabbit	LD50 238 mg/kg		
bis(Dimethylaminoethyl) ether	Inhalation- Vapor (4 hours)	Rat	LC50 2.2 mg/l		
bis(Dimethylaminoethyl) ether	Ingestion	Rat	LD50 570 mg/kg		
Triethylenetetramine	Dermal	Rabbit	LD50 550 mg/kg		
Triethylenetetramine	Ingestion	Rat	LD50 2,500 mg/kg		

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Mercaptan Polymer	Rabbit	No significant irritation
Triethylenetetramine	Rabbit	Corrosive

Serious Eve Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Mercaptan Polymer	Rabbit	Mild irritant
Triethylenetetramine	Rabbit	Corrosive

### **Skin Sensitization**

Name	Species	Value
Mercaptan Polymer	Mouse	Sensitizing
Triethylenetetramine	Guinea	Sensitizing
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Page 6 of

**Germ Cell Mutagenicity** 

Name	Route	Value
Mercaptan Polymer	In Vitro	Not mutagenic

### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Mercaptan Polymer	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
Mercaptan Polymer	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	90 days
Mercaptan Polymer	Ingestion	endocrine system   heart   skin   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

### **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

### **SECTION 15: Regulatory information**

#### 15.1. US Federal Regulations

Contact 3M for more information.

#### **EPCRA 311/312 Hazard Classifications:**

### Physical Hazards

Not applicable

#### Health Hazards

Respiratory or Skin Sensitization

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 05-6630-7
 Version Number:
 18.00

 Issue Date:
 06/26/18
 Supercedes Date:
 06/08/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com



### Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 05-6631-5
 Version Number:
 12.01

 Issue Date:
 04/28/21
 Supercedes Date:
 05/21/18

### **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive DP100 Plus Clear, Part B

### **Product Identification Numbers**

DP-100

### 1.2. Recommended use and restrictions on use

#### Recommended use

Part B of 2-part adhesive, Structural adhesive

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(13)) for consumer paint or coating removal

### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Industrial Adhesives and Tapes Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### **SECTION 2: Hazard identification**

### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

### Signal word

Warning

### **Symbols**

Exclamation mark |

### **Pictograms**



#### **Hazard Statements**

Causes serious eye irritation.

May cause an allergic skin reaction.

### **Precautionary Statements**

### **Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Epoxy Resin	25068-38-6	> 98 Trade Secret *
Organosilane	2530-83-8	< 2 Trade Secret *
Methylene Chloride	75-09-2	< 0.01 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

\_\_\_\_

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Ketones	During Combustion

### **5.3.** Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Methylene Chloride	75-09-2	ACGIH	TWA:50 ppm	A3: Confirmed animal
				carcin.
Methylene Chloride	75-09-2	OSHA	TWA:25 ppm;STEL:125 ppm	29 CFR 1910.1052,
				SKIN

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

### Respiratory protection

None required.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquidColorLight Straw

Specific Physical Form: Viscous

\_\_\_\_\_

**Odor** Epoxy

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data AvailableBoiling PointNot Applicable

Flash Point >=240 °F [Test Method: Closed Cup] [Details: MITS data]

Evaporation rateNot ApplicableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor Pressure0.03 mmHg [@ 20 °C]Vapor DensityNo Data AvailableDensity1.17 g/ml

Specific Gravity1.17 [Ref Std: WATER=1]Solubility in WaterInsoluble [Details: Not soluble]

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data Available

Viscosity 4,000 - 11,000 centipoise [@ 80 °F] [Test Method:Brookfield]

**Hazardous Air Pollutants** 0 % weight [Test Method: Calculated]

Molecular weightNo Data AvailablePercent volatileNo Data Available

**VOC Less H2O & Exempt Solvents** < 10 g/l [Test Method:calculated SCAQMD rule 443.1]

[Details: when used as intended with Part A]

**VOC Less H2O & Exempt Solvents** < 1 % [*Test Method*:calculated SCAQMD rule 443.1]

[Details: when used as intended with Part A]

**VOC Less H2O & Exempt Solvents** < 15 g/l [Test Method:calculated per CARB title 2] [Details:as

supplied]

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

**Substance** Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

No health effects are expected.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### Carcinogenicity:

<u>Ingredient</u>	CAS No.	Class Description	Regulation
Methylene Chloride	75-09-2	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Methylene Chloride	75-09-2	Anticipated human carcinogen	National Toxicology Program Carcinogens
Methylene Chloride	75-09-2	Cancer hazard	OSHA Carcinogens

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Organosilane	Dermal	Rabbit	LD50 4,000 mg/kg
Organosilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Organosilane	Ingestion	Rat	LD50 7,010 mg/kg
Methylene Chloride	Dermal	Rat	LD50 > 2,000 mg/kg
Methylene Chloride	Inhalation- Vapor (4 hours)	Rat	LC50 63.7 mg/l

Page 6 of 1

04/28/21

Methy	ylene Chloride	Ingestion	Rat	LD50 1,410 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant
Organosilane	Rabbit	Mild irritant
Methylene Chloride	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Moderate irritant
Organosilane	Rabbit	Corrosive
Methylene Chloride	Rabbit	Severe irritant

### **Skin Sensitization**

Name	Species	Value
Epoxy Resin	Human	Sensitizing
	and	
	animal	
Organosilane	Guinea	Not classified
	pig	

**Respiratory Sensitization** 

Name	Species	Value
Epoxy Resin	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route Value	
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Organosilane	In vivo	Not mutagenic
Organosilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methylene Chloride	In vivo	Not mutagenic
Methylene Chloride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Organosilane	Dermal	Mouse	Not carcinogenic
Methylene Chloride	Inhalation	Multiple	Carcinogenic
		animal	
		species	

### Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Developmental Effects							
Name	Route	Value	Species	Test Result	Exposure		
					Duration		
Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750	2 generation		
	_	_		mg/kg/day	-		
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750	2 generation		
	_	_		mg/kg/day			

**Page** 7 **of** 11

Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Organosilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Organosilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Organosilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesi s
Methylene Chloride	Inhalation	Not classified for female reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for male reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for development	Multiple animal species	NOAEL 4.3 mg/l	during gestation

## Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methylene Chloride	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours
Methylene Chloride	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Methylene Chloride	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methylene Chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Organosilane	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylene Chloride	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 6.95 mg/l	2 years

Page 8 of 11

Methylene Chloride	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.17 mg/l	2 years
Methylene Chloride	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 35 mg/l	8 weeks
Methylene Chloride	Inhalation	heart	Not classified	Human	NOAEL Not available	
Methylene Chloride	Inhalation	immune system	Not classified	Rat	NOAEL 18 mg/l	28 days
Methylene Chloride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,200 mg/kg/day	3 months
Methylene Chloride	Ingestion	blood	Not classified	Rat	NOAEL 249 mg/kg/day	2 years
Methylene Chloride	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,469 mg/kg/day	3 months
Methylene Chloride	Ingestion	eyes	Not classified	Rat	NOAEL 249 mg/kg/day	104 weeks

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

## **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

.....

## **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

Physical Hazards
Not applicable

Health Hazards		
Respiratory or Skin Sensitization		
Serious eye damage or eye irritation		

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	<u>C.A.S. No</u>	<b>Regulation</b>	<u>Status</u>
Methylene Chloride	75-09-2	Toxic Substances Control Act (TSCA) 6	Applicable
		Banned or Restricted Use Chemicals	

#### **Additional TSCA Information**

Components	CAS No	Additional Information
Methylene Chloride	75-09-2	This chemical/product is not and cannot be distributed in
		commerce (as defined in TSCA section 3(5)) or processed (as
		defined in TSCA section 3(13)) for consumer paint or coating
		removal.

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 05-6631-5
 Version Number:
 12.01

 Issue Date:
 04/28/21
 Supercedes Date:
 05/21/18

\_\_\_\_\_

Page 10 of 11

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com