



ENPAC, LLC TEST REPORT

May 9th, 2024

NOTICE NO: 3677-1299

PRODUCT: Wheeled 95 Poly-Overpack Salvage Drum "X" Rating (ENPAC Part No. 1299-Standard colors)

MANUFACTURER AND TESTING FACILITY: ENPAC, LLC 34355 Melinz Parkway, Eastlake, Ohio 44095

REGULATION: United Nations General Recommendation on Packing for Transportation of Dangerous Goods, 49 CFR §173.3 and 49 CFR §178.601.

ITEMS TESTED: One (1) sample lot of removable, open head, plastic non-bulk packagings.

Packaging type:	1H2	Closure type:	Screw on lid
Manufacturing method	Rotationally molded	Manufacturing method	Rotationally molded
Material of Body:	Medium density polyethylene	Material of closure:	Medium density polyethylene
Rated capacity (l)/(gal):	359.61 L / 95.00 gal.	Closure diameter (cm)/(in):	81.28 cm / 32.00 in.
Overflow capacity (l)/(gal):	361.69 L / 95.55 gal.	Closure height (cm)/(in):	12.70 cm / 5.00 in.
Tare weight-body (kg)/(lb.):	18.62 kg / 41.05 lb.	Tare weight (closure assembly) (kg)/(lb.):	7.05 kg / 15.55 lb. (Lid & Gasket)
Overall diameter-round/handle (cm)/(in):	80.01 cm / 31.50 in. – 91.44 cm / 36.00 in.		
Overall height (cm)/(in):	110.49 cm / 43.50 in		

CONCLUSION: Part design complies and passes all required testing and pertinent regulations as specified in 49 CFR §171 thru 49 CFR §180, and is therefore ENPAC, LLC Certified. Packagings must be filled and used in accordance with all pertinent DOT and UN regulations. Failure to do so renders the qualification invalid and voids all warranties implied or stated.

PACKAGING MARKINGS:

 1H2/X113/S/YY/USA/M6100

YY=Year of Manufacture

APPROVED BY:


(MANAGING MEMBER)


(QUALITY ASSURANCE MANAGER)