

UN SOLIDS TEST REPORT

12.0 Drum with 12.0 Slotted Gasketed Cover

Test Type: Periodic Retest

Additional Package Designs Covered by this report:

12.0 Drum with Non-Slotted Gasketed Cover

Test Report Number: 12DGASLOT-03


Completion Date: 3/9/2024

Test Facility/Packaging Manufacturer

Test Facility: M&M Industries
316 Corporate Place
Chattanooga, TN 37419

Packaging Manufacturer: M&M Industries
316 Corporate Place
Chattanooga, TN 37419


Completed By: 
Title: Quality Assurance Manager

Samples Prepared By: 
QC Tech II


PACKAGE FILL WEIGHT INFORMATION

| | | | |
|------------------------------|-------------|----|-----------------------------|
| Overall package tare weight: | <u>3.6</u> | kg | |
| Filling Substance weight: | <u>36.4</u> | kg | <u>80.25</u> lbs. (Approx.) |
| Package UN weight - Gross: | <u>40</u> | kg | |

UN MARKING



Additional UN Marks covered by this report:






CLOSURE METHOD: PER ATTACHED INSTRUCTIONS

NOTES:

It is the responsibility of the end user to determine authorization for use of the packaging under the Hazardous Materials Regulations.

The use of packaging methods or components other than those documented in this report may render this certification invalid.

| COVER | | DRAWING |
|---|--|--|
| Description | |  |
| Cover Size: | 12.0 | |
| Style: | Drum Cover | |
| Fittings: | N/A | |
| Gasket: | 12.0 - .200"-.240" Dia x 42.125"-44.094" L Neoprene | |
| Wall Thickness: | 0.100 | |
| Method of Manufacture: Injection Molded | | |
| Material: | High Density Polyethylene | |
| Mold # | 12440 | |
| Tare Weight (kg): | 0.88 | |
| Overall Dimensions | | |
| Height: | 2.48" | |
| Top Diameter: | 15.81 | |
| Bottom Diameter: | 16.12 | |
| Thread Dimensions | | |
| Major Diameter: | 15.75" | |
| Minor Diameter: | 15.12" | |
| Markings | M&M Industries, Inc. Chattanooga, TN 37419 Phoenix, AZ 85043 www.ultimatepail.com | |
| | SPI "2" HDPE Recycling Symbol Open/Close Instructions in Multiple Languages | |

| DRUM | | DRAWINGS |
|---|--|--|
| Description | |  |
| Pail Size: | 12.0 | |
| Style: | Drum | |
| Gasket | NA | |
| Method of Manufacture: Injection Molded | | |
| Material: | High Density Polyethylene | |
| Wall Thickness: | 0.140 | |
| Mold# | 12439 | |
| Tare Weight (kg): | 2.72 | |
| Capacity | | |
| Overflow without cover in place (Water)(kgs): | 48.05 | |
| Overall Dimensions | | |
| Height: | 21.37" | |
| Diameter Below Stacking Lug: | 13.95" | |
| Bottom Diameter: | 13.02" | |
| Diameter at Curl (M2 Only): | N/A | |
| Thread Dimensions | | |
| Major Diameter: | 15.62" | |
| Minor Diameter: | 14.83" | |
| Markings | M&M Industries, Inc. Chattanooga, TN 37419 Phoenix, AZ 85043 www.ulitmatepail.com | |
| | SPI "2" HDPE Recycling Symbol | |
| | 12.0 U.S. Gals N.R.C. .140 | |
| |  1H2/Y40/S/24 U.S.A./M2074 | |

DROP TEST CALCULATIONS

| | | | |
|---|-------|----|-----------|
| Maximum Fill Capacity with cover in place(water): | 44.75 | kg | |
| 95% Of Maximum fill Capacity (water): | 42.51 | kg | |
| Overall Package Tare Weight: | 3.6 | kg | |
| Actual Filling substance weight: | 36.4 | kg | 80.25 lb. |
| Package Test Weight: | 40 | kg | 88.18 lb. |

1 lb.= 0.4535924kg 1 kg = 2.204622 lb.

Packing Group Allowed (Chemical): Y(PG II&III) Package Test Level: Y(PG II&III)

Gross Mass (UN Mark on pail) 40 kg

| DROP TEST | | | | |
|----------------------------------|---|---------------------|---------------------------------|------|
| Sample Size: | 6 Samples/3 per orientation | | | |
| Test Contents: | Sand Mesh 2-635 | | | |
| Additional Test Contents: | Vermiculite | 30 Bags | Approx. Weight of Add. Contents | 6 KG |
| Conditioning: | -18 C (0 F) sample temperature at time of test, min. 24 hr. conditioning. | | | |
| Drop Height: | Inches: 48 | Meters: 1.2 (PG II) | 1 m=3.280840 ft. | |
| Test Equipment: | Mechanical Drop Tester and thermometer in filled sample (inside freezer) | | | |
| Test Standard: | Title 49 CFR; Section 178.603 | | | |
| Target: | A rigid, non-resilient, flat and horizontal surface. | | | |

Criteria for passing the test for solids:

Any discharge from a closure is slight and ceases immediately after impact with no further leakage; and no rupture is permitted in packaging's for materials in Class 1 which would permit spillage of loose explosive substances or articles from the outer packaging.

| DROP TEST SET-UP AND RESULTS | | |
|------------------------------|--------|---------|
| Drop Orientation | Sample | Results |
| Diagonal Top Chime | 1 | Pass |
| Diagonal Top Chime | 2 | Pass |
| Diagonal Top Chime | 3 | Pass |
| Flat on Side | 1 | Pass |
| Flat on Side | 2 | Pass |
| Flat on Side | 3 | Pass |

STACKING & STACKING STABILITY TEST CALCULATIONS/RESULTS

| Stack Test Minimum Load Calculation | | | | | | | |
|--|---|------------|---|--------|-----|-----------|-------------|
| Number of packages in a 3m High Stack (118/ Nesting Height (NH)-1) | | | | | | | |
| (118 | / | NH) | = | # | - | -1 | = #3m HS |
| 118 | / | 20.42 | = | 5.78 | - | 1 | = 4.78 |
| Stack Test Load Calculation (Individual Package) | | | | | | | |
| | | Gross Mass | X | #3m HS | = | Load | |
| | | 40 | X | 4.78 | = | 191.20 kg | |
| | | | | | | Appox. | 421.52 lbs. |
| Actual Weight Placed on Pails: | | | | 597.5 | lbs | | 271.02 kgs |

TEST INFORMATION

Stack Test

Test contents: Sand mesh size 2-635
 Additional test contents: Vermiculite 30 bags Approx. Weight of Add. Contents 6 KG
 Conditioning: Standard room temperature/RH
 Equipment: Dead load weight/Guided load fixture
 Test Duration: 24 hours
 Test Standard: Title 49 CFR; Section 178.606

Criteria for passing the Stack Test

No test sample may leak or show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, or cause instability in stacks of packages.

STACK TEST RESULTS

| SAMPLE # | START TIME | DURATION | END TIME | RESULTS |
|----------|------------|----------|----------|---------|
| 1 | 11PM | 24 hours | 11PM | Pass |
| 2 | 11PM | 24 hours | 11PM | Pass |
| 3 | 11PM | 24 hours | 11PM | Pass |

STACK STABILITY RESULTS

| RESULTS | CRITERIA FOR PASSING THE TEST |
|---------|--|
| Pass | <ul style="list-style-type: none"> In guided load tests, stacking stability must be assessed after test completion. Two filled packaging's of the same type must be placed on the test sample The stacked packages must maintain their position for 1 hour. For stack stability, M&M places the filled samples one on top of the other. The bottom sample is rotated to the top until all three samples have been subjected to stacking stability for one hour each |

Additional Drops (If REQUIRED for Variation 5)

Criteria for passing the test for solids

Any discharge from a closure is slight and ceases immediately after impact with no further leakage; and no rupture is permitted in packaging's for materials in Class 1 which would permit spillage of loose explosive substances or articles from the outer packaging.

Description:

| Sample | Drop Orientation | Results |
|--------|--------------------|---------|
| 1 | Diagonal Top Chime | |
| 2 | Diagonal Top Chime | |
| 3 | Diagonal Top Chime | |

Description:

| Sample | Drop Orientation | Results |
|--------|--------------------|---------|
| 1 | Diagonal Top Chime | |
| 2 | Diagonal Top Chime | |
| 3 | Diagonal Top Chime | |

Description:

| Sample | Drop Orientation | Results |
|--------|--------------------|---------|
| 1 | Diagonal Top Chime | |
| 2 | Diagonal Top Chime | |
| 3 | Diagonal Top Chime | |

Description:

| Sample | Drop Orientation | Results |
|--------|--------------------|---------|
| 1 | Diagonal Top Chime | |
| 2 | Diagonal Top Chime | |
| 3 | Diagonal Top Chime | |

M&M INDUSTRIES, INC.

MANUFACTURER'S NOTIFICATION FOR M & M INDUSTRIES, INC. UN/DOT PACKAGING FOR HAZARDOUS SOLIDS General Information:

At M&M Industries, we understand your goal to safely transport your valuable products along roads and highways. You want to provide your customers with value while keeping their trust. While we are legally bound to provide you with the following information, M&M Industries also wants you to know we value your endeavor and want to help you reach your goal, every day.

Under the **U.S. Department of Transportation's Title 49CFR** it is the **Shipper's Responsibility** to determine that the packaging or container is an authorized packaging, including all part 173 requirements. The selected packaging must be properly assembled for transportation in accordance with the manufacturer's notification. **Please do all testing and research necessary to ensure that you have selected the proper M & M Industries container for use with your product.**

To meet UN/DOT Standards, this package must be properly closed for shipment. At the time of transfer, the packaging does not meet the UN standard because it is disassembled. Only when assembled as specified in the closing instructions below, and using the components described herein, is this packaging certified to meet the UN standard. Failure to follow the closing instructions or substituting package components with components other than those identified in the following paragraph will render the UN/DOT Certification invalid.

A copy of the manufacturer's notification, including closing instructions, must be made available for inspection by a representative of the Department of Transportation upon request for at least 90 days once the package is offered to the initial carrier for transportation in commerce. However, M&M Industries recommends that you retain these documents for a minimum of 365 days after the package is offered for shipment. The current record retention requirements are subject to change and are found in 49CFR 173.22(a)(4), <http://www.ecfr.gov>

M&M Industries takes superb pride in our Quality Assurance program and systems. However, even with our best efforts, fittings on covers / pails can become damaged or shift during transportation or storage after leaving our facility. M&M Industries recommends that fillers/offers take all steps deemed necessary to check the fittings on each pail / cover, to meet your quality standards. An example of this is a screw cap on a cover that may vibrate or back off during transportation. The offeror of a hazardous material may be open to liability if they do not take the necessary precautions. Should you have any questions, please contact customer service at **(800) 331-5305**.

THESE CLOSING INSTRUCTIONS REMAIN IN EFFECT UNTIL FURTHER NOTICE.

**CLOSING INSTRUCTIONS FOR:
Life Latch Drum**

Identification of Packaging: This packaging type is identified by:

| Size | Pail ID numbers | Matching lid ID numbers | Lid diameter (Ref only, measured at bottom of lid) |
|-----------|-----------------|-------------------------|--|
| 12 Gallon | 12439,14948 | 12440 | 16.29" |

This packaging may or may not use a gasket and/or vent plug. If a gasket or vent plug is used it must meet the specification below for **SOLIDS**:

UN Markings for Life Latch Drums:

An appropriate UN marking must be maintained for each M&M Industries container design. The UN markings for M&M Industries Life Latch Drum containers are listed below.

| Container Sizes | UN Rating (Without gasket) | UN Rating (With gasket) |
|-----------------|----------------------------|-------------------------|
| 12.0 Gallon | 1H2/Y53/S | 1H2/Y40/S |

In accordance with the U.S. Department of Transportation’s Title 49CFR, Section 178.2, manufacturers of U.N.

Standard/DOT Specification packages are required to notify in writing each person to whom that packaging is transferred of all requirements in this part not met at the time of transfer, and with information specifying the type(s) and dimensions of the closings, including gaskets and any other components needed to ensure that the packaging is capable of successfully passing the applicable performance tests. This information must include any procedures to be followed, including closing instructions for inner packaging and receptacles, to effectively assemble and close the packaging for the purpose of preventing leakage in transportation.

Specifically, the following items pertain to the **Life Latch Drums**:

- **Life Latch Drums** are certified to the UN/DOT performance-oriented packaging standards and are marked with the appropriate UN markings on the container.

- The Life Latch Drum must always be used with the correct Life Latch Drum lid to meet the UN/DOT performance-oriented packaging standards.
- **Life Latch Drums are not UN certified for liquids.**

CLOSING INSTRUCTIONS FOR SOLIDS:

NOTE: This container is not UN certified for liquid hazardous materials

Non-Gasketed lid:

Packaging Components required:

- Drum
- Lid (non-gasketed)

To close: Seat lid on top of drum. Rotate lid counter-clockwise until it drops down (this will help prevent cross-threading). Then, rotate lid clockwise until the raised rectangular mark on the lid (see Figure 1) is located to the left of the raised capsule-shaped marks on the left side of the drum trigger (see Figure 2). Continue rotating until the lid is fully tightened (see Figure 3). Inspect lid after application to confirm it is properly seated.



Figure 1



Figure 2



Figure 3

Gasketed Lid:

Packaging Components required:

- Drum
- Lid (gasketed)

To close: Seat lid on top of drum. Rotate lid counter-clockwise until it drops down (this will help prevent cross-threading). Then, rotate lid clockwise until the raised rectangular

mark on the lid (see Figure 1) is located to the left of the raised circular mark on the right side of the drum trigger (see Figure 2). Continue rotating until the lid is fully tightened. Inspect lid after application to confirm it is properly seated.



FIGURE 1





FIGURE 2

Tamper Evident (Slotted) Gasketed Lid:

To close: Seat lid on top of drum. Rotate lid counter-clockwise until it drops down (this will help prevent cross-threading). Then, rotate lid clockwise until the raised rectangular mark on the lid (see Figure 1) is located to the left of the raised circular mark on the right side of the drum trigger approximately $\frac{1}{4}$ " (see Figure 2). Slot in lid should be lined up even to see the trigger through the window (see Figure 3) Inspect lid after application to confirm it is properly seated.

**FIGURE 1****FIGURE 2**




FIGURE 3

Revision History

| Rev | Description of Change (s) | Written by: | Approved by: | Date: |
|------------|--|--------------------|---------------------|--------------|
| 2 | Changed Gasketed Closing Instructions | Ahron Bobbin | Terry Iker | 1/2/2020 |
| 3 | Added 14948 Mold Number | Ahron Bobbin | Tenna Minwell | 11/14/2021 |
| 4 | Added Tamper Evident Gasketed Lid Closing Instructions. Removed June 2013 on page 1, paragraph 4 | Ahron Bobbin | Kim Holley | 12/23/2022 |